

Hydraulic Folding 5 Gang Rollers

FR5-1040 Premium | FR5-1240 Premium

Five-star performance

Machine Type	FR5-1040 Premium Five Gang Roller								FR5-1240 Premium Five Gang Roller							
	UWF/10/C1	UWB/10/C1	UWF/10/CB4	UWB/10/CB4	UWF/10/LC2	UWB/10/LC2	UWF/10/CB5	UWB/10/CB5	UWF/12/C1	UWB/12/C1	UWF/12/CB4	UWB/12/CB4	UWF/12/LC2	UWB/12/LC2	UWF/12/CB5	UWB/12/CB5
Product code	UWF/10/C1	UWB/10/C1	UWF/10/CB4	UWB/10/CB4	UWF/10/LC2	UWB/10/LC2	UWF/10/CB5	UWB/10/CB5	UWF/12/C1	UWB/12/C1	UWF/12/CB4	UWB/12/CB4	UWF/12/LC2	UWB/12/LC2	UWF/12/CB5	UWB/12/CB5
Working width	10.40m (34')	10.40m (34')	10.40m (34')	10.40m (34')	10.40m (34')	10.40m (34')	10.40m (34')	10.40m (34')	12.40m (41')	12.40m (41')	12.40m (41')	12.40m (41')	12.40m (41')	12.40m (41')	12.40m (41')	
Brakes	Braked axles		Braked axles		Braked axles		Braked axles		Braked axles		Braked axles		Braked axles		Braked axles	
Ring Type	C	C	CB	CB	C	C	CB	CB	C	C	CB	CB	C	C	CB	CB
Diameter of rings	55cm (22")	55cm (22")	55cm (22")	55cm (22")	61cm (24")	61cm (24")	61cm (24")	61cm (24")	55cm (22")	55cm (22")	55cm (22")	55cm (22")	61cm (24")	61cm (24")	61cm (24")	61cm (24")
Key to ring types:	C = Cambridge Rings CB = Cambridge Breaker Rings LC = Large Cambridge Rings															



Premium heavy-duty five-gang rollers available in a choice of 10.40m and 12.40m working widths with braked axles, and four different ring configurations.

Designed for large scale farmers and contractors, the rollers are equipped with Twose's innovative weight transfer system across each section, five individual pivot points for close-contour following, and smooth folding for a rapid transition to and from transport mode.

Strength and durability are boosted by an exceptionally robust design, triple sealed bearings, and a pressure relief system which protects the rams when working on very uneven ground.

Key features

- 10.40m (34' 0") and 12.40m (41' 0") working widths
- Trailed

Performance features

- Super-strength mainframe
- Designed for professional contractors
- Outstanding productivity
- Large wheels and tyres for smooth road transport
- Pivoting wing sections for effective contour-following
- Choice of two different rings

User friendly

- Easy adjustment of rings
- One-touch hydraulic folding for safe transport

Reliability and protection

- Pressure relief system protects the rams on uneven terrain
- Robust fabricated steel frame
- Hand-built in the UK
- Triple sealed bearings for enhanced durability
- Reinforced drawbar

Markets

- Contractors, professionals

Tractor requirements

- From 200hp (FR5-1040 Premium)

FR5-1040 Premium

t : 01884 253691
w : www.twose.com
e : sales@twose.com